



# 2.5 x 2.0mm Auto Grade Crystal C2BA

(former FXA2520B)

## DATASHEET

• SPECIFICATIONS	
PARAMETERS	MAX (unless otherwise noted)
Frequency Range	16.000 ~ 50.000 MHz
Frequency Tolerance @ 25°C	±10 PPM ~ ±50 PPM (See options on page 2)
Frequency Stability, ref @ 25°C	±20 PPM ~ ±100 PPM (See options below)
Temperature Range	
Operating (TOPR)	-40°C ~ +125°C (see options below)
Storage (TSTG)	-55°C ~ +150°C
Shunt Capacitance (Co)	3pF
Load Capacitance (CL)	7pF~Series (See options on page 2)
Drive Level	100µW
Aging per year	±5 PPM
Maximum Soldering Temp / Time	260°C / 10 Seconds
Moisture Sensitivity Level (MSL)	1
Termination Finish	Au
Seal Method	Seam Seal
Lead (Pb) Free	Yes
RoHS Compliant	No Exemptions


Frequency Range (MHz)	Operating Mode	Max ESR Ω
16.000000 ~ 30.000000	Fundamental	200
30.000001 ~ 50.000000	Fundamental	100

Note: Dimensional drawing is for reference to critical specifications defined by size measurements. Certain non-critical visual attributes, such as side castellations, etc. may vary. Other tolerances, stabilities and temperature ranges available.

### •Other Stabilities Available

Stability Temperature	±20 PPM	±30 PPM	±50 PPM	±100 PPM
-40 ~+85°C	O	O	O	O
-40 ~+105°C	X	X	O	O
-40 ~+125°C	X	X	O	O

Key: O=Available, X=Not Available, Δ=Consult Fox Technical Support





# 2.5 x 2.0mm Auto Grade Crystal C2BA

(former FXA2520B)

## DATASHEET

• TAPE SPECIFICATIONS (millimeters)							• REEL SPECIFICATIONS (millimeters)								
MODEL	A	B	C	D	E	F	STD Reel QTY	MODEL	G	H	I	J	K	L	M
C2BA	∅1.0	4.0	4.0	3.5	8.0	0.8	3,000	C2BA	2.5	∅13	∅21	∅60.2	∅178	8.1	1.6

**Available Options & Part Identification for Automotive Crystal Model Number C2BA**

E C2BA C B E S 16.0

<b>F</b>	<b>C2BA</b>	<b>C</b>	<b>B</b>	<b>E</b>	<b>S</b>	<b>16.0</b>
FOX	Model Number	Tolerance B=50ppm <b>C=30ppm</b> E=20ppm H=10ppm	Stability A=100ppm <b>B=50ppm</b> C=30ppm E=20ppm	Load Capacitance A=Series V=7pF D=8pF <b>E=10pF</b> G=12pF J=15pF K=16pF L=18pF M=20pF	Operating Temperature M=-40~+ 85°C P=-40~+105°C <b>I=-40~+125°C</b>	Frequency



### Corporate Headquarters

5570 Enterprise Parkway  
Fort Myers, FL 33905  
<http://www.FOXONLINE.com>

### Sales

1-888-GET-2-FOX (1-888-438-2369) or  
1-239-693-0099  
<http://www.FOXONLINE.com/repdisty>

### Tech Support

<http://www.FOXONLINE.com/email>

**PRODUCT USE:** Fox Electronics reserves the right to modify the products and/or specifications described herein at any time and at Fox Electronics' sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of Fox Electronics' products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of Fox Electronics or any third parties.

Fox Electronics' products are not intended for use in applications involving extreme environmental conditions or in life support systems or similar devices where the failure or malfunction of a Fox Electronics product can be reasonably expected to significantly affect the health or safety of users. Anyone using a Fox Electronics product in such a manner does so at their own risk, absent an express, written agreement by Fox Electronics.

Fox Electronics and the Fox logo are registered trademarks of Fox Electronics. Product specification is subject to change without notice. Other trademarks and service marks used herein, including protected names, logos and designs, are the property of Fox Electronics or their respective third party owners.

For datasheet type definitions and a glossary of common terms, visit <http://www.foxonline.com/tgcrystals.html>.