


ISSUE 2; September 2016

Description

- Standard 1.6 x 1.2mm SMD crystal in a hermetically sealed ceramic package with a sealed metal lid

Frequency Parameters

- Frequency: 24.0MHz to 80.0MHz
 - Frequency Tolerance: $\pm 10.00\text{ppm}$ to $\pm 100.00\text{ppm}$
 - Tolerance Condition: @ 25°C
 - Frequency Stability: $\pm 10.00\text{ppm}$ to $\pm 100.00\text{ppm}$
 - Ageing: $\pm 5\text{ppm}$ max per year @ 25°C
 - Developed frequencies: 24.0MHz, 26.0MHz, 27.0MHz, 27.120MHz, 32.0MHz, 36.0MHz, 37.40MHz, 38.40MHz, 40.0MHz, 48.0MHz
- Crystals have been developed at the above frequencies and with the following specification -
Tolerance: $\pm 10\text{ppm}$
Stability:
 $\pm 15\text{ppm}$ over -20 to 70°C
 $\pm 30\text{ppm}$ over -40 to 85°C
- For alternative frequencies and specifications please contact an IQD Sales Office



Electrical Parameters

- Load Capacitance (CL): 10.0pF to 30.0pF
- Shunt Capacitance (C0): 7pF max
- Drive Level: 100µW max
- Note: ESR values for reference only - the final specification shall be confirmed for each frequency after sample production

Operating Temperature Ranges

- 0 to 50°C
- 10 to 60°C
- 20 to 70°C
- 40 to 85°C


Environmental Parameters

- Storage Temperature Range: -40 to 85°C
- Shock: IEC 60068-2-27: 1000G, 1ms, 3 times in each of 3 mutually perpendicular planes
- Vibration: IEC 60068-2-6: 1.5mm amplitude, 10Hz-55Hz, 1min in 3 mutually perpendicular planes, duration 2hrs each plane (total 6hrs)

Ordering Information

- Frequency*
- Model*
- Frequency Tolerance (@ 25°C)*
- Frequency Stability (over operating temperature range)*
- Operating Temperature Range*
- Load Capacitance*
- Overtone
- (*minimum required)
- Example
- 32.0MHz IQXC-26
- 30/30/-40 to 85C/16 FUND

Outline (mm)



Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

Compliance

- RoHS Status (2011/65/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

Packaging Details

- Pack Style: Reel Tape & reel in accordance with EIA-481-D
 Pack Size: 3,000
- Pack Style: Cutt In tape, cut from a reel
 Pack Size: 100
- Pack Style: Bulk Loose in bulk pack
 Pack Size: 100

Electrical Specification - maximum limiting values

Frequency Min	Frequency Max	Temperature Range	Stability Min*	Over Tone Order	ESR
		°C	ppm		Ω
24.0MHz	30.0MHz	0 to 50	±10	Fundamental	200
		-10 to 60	±10		
		-20 to 70	±20		
		-40 to 85	±30		
30.000001MHz	80.0MHz	0 to 50	±10	Fundamental	100
		-10 to 60	±10		
		-20 to 70	±20		
		-40 to 85	±30		

*Stability Maximum values ±100ppm

This document was correct at the time of printing; please contact your local sales office for the latest version.
[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200
 Germany: 0800 1808 443

France: 0800 901 383
 USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
 Web: www.iqdfrequencyproducts.com