

# G Series Crystal



- 5mm X 7mm X 4 Pads Ceramic Package
- Wide Frequency Range
- Tight Tolerance and Stability
- Tape and Reel Packaging



Frequency Range	6.000MHZ to 100.000MHZ
Frequency Tolerance / Stability	(See Part Number Guide for Options)
Operating Temperature Range	(See Part Number Guide for Options)
Storage Temperature	-40°C to +85°C
Aging	±5ppm / first year Max
Shunt Capacitance	7pF Max
Load Capacitance	20pF Standard (See Part Number Guide for Options)
Equivalent Series Resistance	See ESR Chart
Mode of Operation	Fundamental, or 3 <sup>rd</sup> OT
Drive Level	100µW Typical
Insulation Resistance	500 Megaohms Min at 100VDC

## Environmental & Mechanical Detail

Shock	MIL-STD-883, Method 2002 Cond B
Solderability	MIL-STD-883, Method 2003
Solvent Resistance	MIL-STD-202, Method 215
Vibration	MIL-STD-883, Method 2007, Cond A
Gross Leak Test	MIL-STD-883, Method 1014, Cond C
Fine Leak Test	MIL-STD-883, Method 1014, Cond A2
MSL	Level 1 per IPC/JEDEC J-STD 20

## Marking Detail

Line 1: MXX.XXX
XX.XXX = Frequency in MHz
Line 2: SYMCCL
S = Internal Code
YM = Numerical Date Code (Year/ Month)
CC = Crystal Parameters Code
L = Denotes RoHS Compliant



**MMD MONITOR/QUARTZEK – An ILSI Company,**  
 5458 Louie Lane, Reno, NV 89511  
 Phone: (775) 851-8880, [www.mmdcomp.com](http://www.mmdcomp.com)



Revision:	07/10/13 J
-----------	------------

