

**QUARTZ CRYSTAL UNIT IN CERAMIC SEAM SEAL SMD PACKAGE, SIZE 6.0 X 3.5MM.**


**S6CA**

**PRODUCT FEATURES**

- SMALL PACKAGE SIZE 6.0 X 3.5 X 1.0MM WITH 2 PADS.
- EXCELLENT HEAT AND SHOCK RESISTANCE.
- HIGHLY RELIABLE SEAM SEAL PACKAGE AND LOW AGING.
- AUTOMOTIVE GRADE COMPLIANT TO AEC-Q200 IS AVAILABLE.

**APPLICATIONS**


- MICROPROCESSOR
- LAN, WLAN, MODEM
- MOBIL COMMUNICATION
- PORTABLE DEVICES.



**PRODUCT SPECIFICATIONS**

PARAMETER	SYMBOL	SPECIFICATIONS	REMARKS
FREQUENCY RANGE	$F_N$	<b>7.5 ~ 150.0MHZ</b>	FUNDAMENTAL UP TO 60MHZ
OPERATION MODE	—	FUNDAMENTAL / 3RD OVERTONE	OVERTONE ABOVE 36MHZ
FREQUENCY TOLERANCE	$\Delta f/f$	$\pm 10\text{PPM}$ , $\pm 20\text{PPM}$ , $\pm 30\text{PPM}$ , $\pm 50\text{PPM}$	OTHER OPTIONS AVAILABLE
STABILITY OVER OPERATING TEMP.	$T_C$	$\pm 10\text{PPM}$ , $\pm 20\text{PPM}$ , $\pm 30\text{PPM}$ , $\pm 50\text{PPM}$	DEPENDING ON OPERATING TEMPERATURE RANGE
OPERATING TEMPERATURE RANGE	$T_{OP}$	$-20^\circ\text{C} \sim +70^\circ\text{C}$ OR $-40^\circ\text{C} \sim +85^\circ\text{C}$	OTHER OPTIONS AVAILABLE
LOAD CAPACITANCE	CL	8 TO 32PF OR SERIES	PLEASE SPECIFY LOAD CAPACITANCE
EQUIVALENT SERIES RESISTANCE	ESR	100Ω MAX 80Ω MAX 60Ω MAX 50Ω MAX 45Ω MAX 40Ω MAX 100Ω MAX	FUND MODE 7.5 ~ 8MHZ FUND MODE 8 ~ 12MHZ FUND MODE 10 ~ 12MHZ FUND MODE 12 ~ 16MHZ FUND MODE 16 ~ 20MHZ FUND MODE 20 ~ 60MHZ 3RD OT MODE 36 ~ 150MHZ
DRIVE LEVEL	DL	100μW TYP, 300μW MAX	—
AGING FIRST YEAR	$\Delta f/y_1$	$\pm 5\text{PPM}$	@+25°C

**MECHANICAL DIMENSIONS**



QUARTZ CRYSTAL UNIT IN CERAMIC SEAM SEAL SMD PACKAGE, SIZE 6.0 X 3.5MM.


S6CA

ENVIRONMENTAL COMPLIANCE INFORMATION

- ROHS 6/6 COMPLIANT (DIRECTIVE 2011/65/EC) AND LEAD-FREE.
- COMPLIANT TO ROHS 2 (DIRECTIVE 2018/863) (ALSO CALLED ROHS10).
- HALOGEN-FREE PER DEFINITION OF IEC 61249-2-21 2033.
- NONE-USE OF SVHCS PER REACH IS CURRENTLY GIVEN, CONTINUOUSLY MONITORED AND UPDATED AS THE COMMISSION ISSUES NEW RELEASES.
- PRODUCT DOES NOT CONTAIN ANY PHTHALATES (PHS).
- PRODUCT DOES NOT CONTAIN PVC (POLYVINYL CHLORIDE).
- PRODUCT DOES NOT CONTAIN PFOS/PFOA NOR BEING SAME USED TO MANUFACTURE THE COMPONENTS OF THIS PRODUCT.
- NONE-USE OF CONFLICT MINERALS PER THE DODD-FRANK WALL STREET REFORM AND CONSUMER PROTECTION ACT (WALL STREET REFORM ACT).




SOLDERING RECOMMENDATIONS



PACKAGING INFORMATION


- PACKAGING IN TAPE & REEL IN COMPLIANCE TO EIA-481.
- QTY PER REEL: 1,000PCS
- REEL DIA A=180MM.
- EMBOSSED CARRIER TAPE WIDTH W = 12MM.
- COMPONENT PITCH P1 = 8MM.



PART NUMBER SYNTAX

- PART NUMBER FAMILY (REPRESENTS PRODUCT MODEL AND PACKAGE SIZE / TYPE)
- NOMINAL FREQUENCY (IN MHZ WITH AT LEAST FOUR DIGITS AFTER DECIMAL POINT)
- OPERATION MODE CODE (F = FUNDAMENTAL / T = 3RD OVERTONE)
- LOAD CAPACITANCE (ACTUAL VALUE OR SS FOR SERIES)
- OPERATING TEMPERATURE RANGE CODE (I.E. C= -10~60°C, E= -20~70°C, M= -40~85°C)
- FREQUENCY TOLERANCE DESIGNATOR (I.E. 1=10PPM, 2=20PPM, Y=15PPM, Z=25PPM)
- FREQUENCY STABILITY DESIGNATOR (I.E. 1=10PPM, 2=20PPM, Y=15PPM, Z=25PPM)
- PART NUMBER EXTENSION (ONLY FOR NONE-STANDARD OR CUSTOMIZED PART)

S6CA 25.0000 F 18 E 23 -EXT



FOR MORE INFORMATION PLEASE CONTACT US.

HONG KONG:  
NAKAGAWA ELECTRONICS LIMITED  
+852 2389 9201 sales@nkg.com.hk  
+852 2341 0001 www.nkg.com.hk

China Shenzhen office:  
深圳中川晶体电子有限公司  
+86(0)755 2598 2648 sales\_sz@nkg.cn  
+86(0)755 2598 2390 www.nkg.com.hk

China Suzhou office:  
苏州纳美电子有限公司  
+86(0)512 8818 7890 sales\_nm@nkg.cn  
+86(0)512 8818 7889 www.nkg.com.hk