

ASO72P / ASO73P LVPECL Compatible

2.5 Volt and 3.3 Volt 7x5mm Surface Mount Ceramic Crystal Oscillator

Applications:

- SONET/SDH
- 1G/10G Ethernet
- Wideband WLAN AP
- Fiber Channel
- XDSL

FEATURES

- LVPECL Complementary output
- Low phase jitter (12KHz to 20MHz) under 1 ps or 4 ps (RMS)
- Special side-pad design for jitter improvement option
- Low profile package design (2.0mm height max.)
- RoHS Compliant

SPECIFICATION

MODEL		ASO72P	ASO73P
Frequency Range	MHz	25.000~800.000	
Frequency Stability*	ppm	±25~±100	
Temperature Range			
Operating Temp	°C	-10 to +70	-10 to +70
Storage Temp	°C	-55 to +125	-55 to +125
Power Supply Voltage	VDC	+2.5±5%	+3.3±10%
Output Voltage High (V OH)	V (Min)	1.475	2.275
Output Voltage Low (V OL)	V (Max)	1.095	1.680
Output Load	Ω	50	50
Output Symmetry	%	45~55%	
Input Current			
25~100MHz	mA (Max.)	60	60
101~160MHz		65	65
161~800MHz		100	100
Input Voltage			
Enable High Input Voltage	V (Min)	1.75	2.31
Enable Low Input Voltage	V (Max)	0.75	0.99
Rise / Fall Time (20% / 80%)			
40~100MHz	nS (Max.)	1.0	1.0
101~160MHz		0.5	0.5
161~800MHz		1.0	1.0
Aging	ppm/Year	±3	

* Inclusive of 25°C±3°C & Operating Temperature Range.

ENABLE / DISABLE FUNCTION


INH (# 1)	Q (# 4) & QN(#5)
HIGH (Open)	Operating
Low	High impedance

PART NUMBERING GUIDE

Example: ASO72P-106.25M-F2T

MODEL	Frequency	Stability	OP Temp Range	Tristate
ASO72P ASO73P	In MHZ	D: ±25ppm E: ±30ppm F: ±50ppm G: ±100ppm O: Others	1: 0 to +70°C 2: -10 to +70°C 3: -20 to +70°C 4: -20 to +80°C 5: -40 to +85°C 6: -40 to +105°C 0: Others	T: Tristate N: Non-Tristate

DIMENSION (mm)



C1*: A 0.01uF or 0.1uF decoupling capacitor is recommended.

C2**: By-pass capacitor for the noise suppression. (please contact our engineer dept. for the recommended capacitor value)

MARKING RULE

