

HCMOS 2.5x2mm 2.5V Oscillator



Model: F240 SERIES

RoHS Compliant / Pb Free

Rev. 12/2010

Page 1 of 2

http://www.foxonline.com/need_a_sample.htm



FEATURES

- 2.5V Operation
- Standby Function
- Tape and Reel (3,000 pcs. STD)

• PART NUMBER SELECTION [Learn More](#) - Internet Required

Part Number	Model Number	Frequency Stability ¹	Operating Temperature (°C)	Frequency Range (MHz)
778-Frequency-xxxxx	F240	±100PPM	-20 ~ +70	0.750 ~ 50.000
778R-Frequency-xxxxx	F240R	±100PPM	-40 ~ +85	0.750 ~ 50.000
779-Frequency-xxxxx	F245	±50PPM	-20 ~ +70	0.750 ~ 50.000
779R-Frequency-xxxxx	F245R	±50PPM	-40 ~ +85	0.750 ~ 50.000
780-Frequency-xxxxx	F246	±25PPM	-20 ~ +70	0.750 ~ 50.000

• ELECTRICAL CHARACTERISTICS

PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	0.750 ~ 50.000 MHz
Storage Temperature Range (T _{STG})	-55°C ~ +100°C
Supply Voltage (V _{DD})	2.5V ± 5%
Input Current (I _{DD})	
0.750 ~ 19.999 MHz	5mA
19.999+ ~ 39.999 MHz	9mA
39.999+ ~ 50.000 MHz	11mA
Output Symmetry (50% V _{DD})	40% ~ 60%
Rise Time (10% ~ 90% V _{DD}) (T _R)	10nS
Fall Time (90% ~ 10% V _{DD}) (T _F)	10nS
Output Voltage (V _{OL})	10% V _{DD}
(V _{OH})	90% V _{DD} Min
Output Current (I _{OL})	4mA Min
(I _{OH})	-4mA Min
Output Load (HCMOS)	15pF
Standby Current	5µA
Start-up Time (T _s)	10mS
Output Disable Time ²	200nS
Output Enable Time ²	10mS
Aging (T _a =25°C: per year)	± 5 PPM
Reflow Soldering Temp	260°C / 10 Seconds
Moisture Sensitivity Level (MSL)	1
Termination Finish	Au


¹ Inclusive of 25°C tolerance, operating temperature range, input voltage change, load change, shock, and vibration.

² An internal pullup resistor from pin 1 to pin 4 allows active output if pin 1 is left open.

Note: A 0.01µF capacitor should be placed between V_{DD} (Pin 4) and GND (Pin2) to minimize power supply noise. All specifications subject to change without notice.

Drawing is for reference to critical specifications defined by size measurements.

Certain non-critical visual attributes, such as side castellations, reference pin shape, etc. may vary. All specifications subject to change without notice.



• ENABLE / DISABLE FUNCTION

INH (Pin 1)	OUTPUT (Pin 3)
OPEN	ACTIVE
'1' Level V _{IH} ≥ 80% V _{DD}	ACTIVE
'0' Level V _{IL} ≤ 20% V _{DD}	High Z

HCMOS 2.5x2mm 2.5V Oscillator



Model: F240 SERIES

RoHS Compliant / Pb Free

Rev. 12/2/2010

Page 2 of 2

http://www.foxonline.com/need_a_sample.htm



• TAPE SPECIFICATIONS (millimeters)							
MODEL	A	B	C	D	E	F	STD Reel QTY
F240 Series	∅1.5	4.0	4.0	3.5	8.0	1.15	3,000

• REEL SPECIFICATIONS (millimeters)							
MODEL	G	H	I	J	K	L	M
F240 Series	2.0	∅13	∅21	∅60	∅180	9.0	2.0

