




# 5.0mm x 3.2mm SMD Crystal

**C5BQ**  
(former FQ5032B)  
**DATASHEET**

- Tolerances down to 20 PPM
- Stabilities down to 20 PPM
- Operating Temperature Ranges up to -40°C ~ +85°C

• C5BQ STANDARD SPECIFICATIONS	
PARAMETERS	MAX (unless otherwise noted)
Frequency Range (Fo)	8.000 ~ 60.000 MHz
Frequency Tolerance @ 25°C	(See options on page 2)
Frequency Stability, ref @ 25°C Over Operating Temp Range	(See options below)
Temperature Range	
Operating (TOPR)	(See options below)
Storage (TSTG)	-40°C ~ +85°C
Shunt Capacitance (Co)	5 pF
Load Capacitance (CL)	(See options on page 2)
Drive Level	0.5 mW
Aging per year	±5 PPM
Termination Finish	Au
Seam Method	Resin
Lead (Pb) Free	Yes
RoHS Compliant	Yes

Frequency Range (MHz)	Operating Mode	Max ESR Ω
8.000000 ~ 11.999999	Fundamental	100
12.000000 ~ 16.000	Fundamental	80
16.000001 ~ 48.000	Fundamental	50
48.000001 ~ 60.000	3rd OT	100



Note: Dimensional drawing is for reference to critical specifications defined by size measurements. Certain non-critical visual attributes, such as side castellations, etc. may vary.

## • Available Operating Temperatures and Stabilities\*

Stability Temperature	±15 PPM	±20 PPM	±25 PPM	±30 PPM	±50 PPM
0 ~+70°C	Δ	○	○	○	○
-20 ~+70°C	Δ	○	○	○	○
-40 ~+85°C	X	X	○	○	○

Key: O=Available, X=Not Available, Δ=Consult Fox Technical Support

\*Does not imply a stocked part.

<p>© Copyright 2017 Fox Electronics. All rights reserved</p>	<b>Title / Description:</b> C5BQ SERIES STANDARD SPECIFICATIONS			
	<b>Drawing Number:</b> 101146		<b>Size:</b> A	
	<b>Part Number:</b>		<b>Cage:</b> 61429	
	<b>Draftsperson:</b> CMR	<b>Approved:</b> RB	<b>Revision Date:</b> 2/28/2017	




# 5.0mm x 3.2mm SMD Crystal

**C5BQ**  
(former FQ5032B)  
**DATASHEET**

• TAPE SPECIFICATIONS (millimeters)							
MODEL	A	B	C	D	E	F	STD Reel QTY
C5BQ	∅1.5	4.0	8.0	5.5	12.0	1.5	1,000

• REEL SPECIFICATIONS (millimeters)							
MODEL	G	H	I	J	K	L	M
C5BQ	2.0	∅13	∅21	∅62	∅180	13.5	2.0



Available Options & Part Identification for SMD Crystal C5BQ*						
<b>F C5BQ C C M C 25.000</b>						
<b>F</b>	<b>C5BQ</b>	<b>C</b>	<b>C</b>	<b>M</b>	<b>C</b>	<b>25.000</b>
<b>FOX</b>	<b>Model Number</b>	<b>Tolerance</b> B=50ppm C=30ppm D=25ppm E=20ppm	<b>Stability</b> B=50ppm C=30ppm D=25ppm E=20ppm F=15ppm**	<b>Load Capacitance</b> A=Series V=7pF D=8pF E=10pF G=12pF J=15pF K=16pF L=18pF <b>M=20pF</b>	<b>Operating Temperature</b> C=0 to +70C F=-20 to +70C M=-40 to +85C	<b>Frequency (MHz)</b>

\*Not all frequency, tolerance, stability, load, and operating temperature combinations may be available.

<p>© Copyright 2017 Fox Electronics, All rights reserved</p>	<b>Title / Description:</b> C5BQ SERIES STANDARD SPECIFICATIONS		
	<b>Drawing Number:</b> 101146		<b>Size:</b> A
	<b>Part Number:</b>		<b>Cage:</b> 61429
	<b>Draftsperson:</b> CMR	<b>Approved:</b> RB	<b>Revision Date:</b> 2/28/2017



# 5.0mm x 3.2mm SMD Crystal

# C5BQ

(former FQ5032B)  
DATASHEET

• C5BQ (Former FQ5032B) Standard Crystals					
Part Number	Frequency	Tolerance	Stability	Temp Range	CL
FQ5032B-10.000	10.000000	+/- 30 ppm	+/- 30 ppm	0 to +70 C	20pF
FQ5032B-12.000	12.000000	+/- 30 ppm	+/- 30 ppm	0 to +70 C	20pF
FQ5032B-16.000	16.000000	+/- 30 ppm	+/- 30 ppm	0 to +70 C	20pF
FQ5032B-20.000	20.000000	+/- 30 ppm	+/- 30 ppm	0 to +70 C	20pF
FQ5032B-24.000	24.000000	+/- 30 ppm	+/- 30 ppm	0 to +70 C	20pF
FQ5032B-25.000	25.000000	+/- 30 ppm	+/- 30 ppm	0 to +70 C	20pF
FQ5032BR-10.000	10.000000	+/- 30 ppm	+/- 50 ppm	-40 to +85 C	20pF
FQ5032BR-12.000	12.000000	+/- 30 ppm	+/- 50 ppm	-40 to +85 C	20pF
FQ5032BR-16.000	16.000000	+/- 30 ppm	+/- 50 ppm	-40 to +85 C	20pF
FQ5032BR-20.000	20.000000	+/- 30 ppm	+/- 50 ppm	-40 to +85 C	20pF
FQ5032BR-24.000	24.000000	+/- 30 ppm	+/- 50 ppm	-40 to +85 C	20pF
FQ5032BR-25.000	25.000000	+/- 30 ppm	+/- 50 ppm	-40 to +85 C	20pF



Corporate  
Headquarters  
5570 Enterprise Parkway  
Fort Myers, FL 33905  
<http://www.FOXONLINE.com>

Sales  
1-888-GET-2-FOX (1-888-438-2369) or  
1-239-693-0099  
<http://www.FOXONLINE.com/repdisty>

Tech Support  
<http://www.FOXONLINE.com/email>

PRODUCT USE: Fox Electronics reserves the right to modify the products and/or specifications described herein at any time and at Fox Electronics' sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied, including, but not limited to, the suitability of Fox Electronics' products for any particular purpose, an implied warranty of merchantability, or non-infringement of the intellectual property rights of others. This document is presented only as a guide and does not convey any license under intellectual property rights of Fox Electronics or any third parties.

Fox Electronics' products are not intended for use in applications involving extreme environmental conditions or in life support systems or similar devices where the failure or malfunction of a Fox Electronics product can be reasonably expected to significantly affect the health or safety of users. Anyone using a Fox Electronics product in such a manner does so at their own risk, absent an express, written agreement by Fox Electronics.

Fox Electronics and the Fox logo are registered trademarks of Fox Electronics. Product specification is subject to change without notice. Other trademarks and service marks used herein, including protected names, logos and designs, are the property of Fox Electronics or their respective third party owners.

For datasheet type definitions and a glossary of common terms, visit <http://www.foxonline.com/tgcrystals.html>.

	<b>Title / Description:</b> C5BQ SERIES STANDARD SPECIFICATIONS		
	<b>Drawing Number:</b> 101146		<b>Size:</b> A
	<b>Part Number:</b>		<b>Cage:</b> 61429
	<b>Draftsperson:</b> CMR	<b>Approved:</b> RB	<b>Revision Date:</b> 2/28/2017