



FEATURES

- AT-cut crystal performance
- Wide frequency range
- Standard and moderate precision available
- Low profile package
- AEC-Q200 Qualified



Parameters		Specifications
Nominal Frequency Range 標稱頻率範圍	f_0	3.5MHz ~ 40.0MHz (Fundamental) 30.0MHz ~ 80.0MHz (3rd Overtone)
Frequency Tolerance, Ta=25°C ± 3°C 常溫頻率偏差	$\Delta f/f$	±10ppm, ±30ppm
Load Capacitance 負載電容	C_L	18pF or customer specify
Frequency Tolerance over Operating Temperature Range with refer to 25°C 相對於常溫的頻率溫度特性	$\Delta f/f$	±10ppm, ±30ppm
Operating Temperature Range 工作溫度範圍	T_{OPR}	-20°C ~ +70°C, -40°C ~ +85°C
Storage Temperature Range 儲存溫度範圍	T_{STG}	-55°C to 125°C
Drive Level 激勵功率	DL	0.1mW (1mW Max.)
Shunt Capacitance 靜態電容	C_0	7pF Max.
Insulation Resistance 絕緣電阻	IR	500MΩ Min.
Aging 老化率	Δf_A	±5ppm/Year Max.

SERIES RESISTANCE (ESR) 串聯諧振阻抗						
Frequency Range	$3.5 < f_0 \leq 4.5$	$4.5 < f_0 \leq 6$	$6 < f_0 \leq 8$	$8 < f_0 \leq 12$	$12 < f_0 \leq 15$	$15 < f_0 \leq 18$
ESR	120Ω Max.	90Ω Max.	70Ω Max.	60Ω Max.	40Ω Max.	30Ω Max.

Frequency Range	$18 < f_0 \leq 40$	$30 < f_0 \leq 35$ (3.O.T)	$35 < f_0 \leq 40$ (3.O.T)	$40 < f_0 \leq 80$ (3.O.T)
ESR	25Ω Max.	100Ω Max.	80Ω Max.	70Ω Max.

Please consult our sales representatives for other specifications.
如對其他規格查詢，請與我司銷售人員聯繫

DIMENSION (mm)

Series	Height (H)
THHF-49S3	3.5mm Max.
THHF-49S2A	2.5mm Max.
THHF-49S2B	2.3mm Max.

THHF-49S3/THHF-49S2A/THHF-49S2B

All specifications are subject to change without prior notice.
本公司保留修改規格的權利。

