

ISSUE 4; April 2016

**Description**

- 4 x 2.5mm SMD crystal in a hermetically sealed ceramic package with a seam sealed metal lid. Often used in Bluetooth, ZigBee and similar RF applications.

**Frequency Parameters**

- Frequency 12.0MHz to 50.0MHz
- Frequency Tolerance  $\pm 10.00\text{ppm}$  to  $\pm 50.00\text{ppm}$
- Tolerance Condition @ 25°C
- Frequency Stability  $\pm 10.00\text{ppm}$  to  $\pm 50.00\text{ppm}$
- Ageing  $\pm 3\text{ppm}$  max per year @ 25°C
- Developed Frequencies: 12.0MHz, 13.0MHz, 13.560MHz, 14.318180MHz, 14.74560MHz, 16.0MHz, 16.93440MHz, 18.4320MHz, 19.66080MHz, 20.0MHz, 24.5760MHz, 25.0MHz, 26.0MHz, 27.0MHz, 27.120MHz & 29.020MHz.

**Electrical Parameters**

- Load Capacitance (CL) 9.0pF to 30.0pF
- Shunt Capacitance (C0) 5pF max
- Drive Level 100µW max

**Operating Temperature Ranges**

- 10 to 60°C
- 20 to 70°C
- 40 to 85°C

**Environmental Parameters**

- Storage Temperature Range: -40°C to 90°C
- Drop: 75cm drop (3 times) onto hard wooden board.
- Vibration: 1.5mm amplitude, 10Hz-55Hz, 1min in 3 mutually perpendicular planes, duration 2hrs each plane.

**Ordering Information**

- Frequency\*
- Model\*
- Frequency Tolerance (@ 25°C)\*
- Frequency Stability (over operating temperature range)\*
- Operating Temperature Range\*
- Load Capacitance\*
- Overtone
- (\*minimum required)
- Example  
20.0MHz CFPX-201  
50/50/-10 to 60C/10 FUND

**Compliance**




- RoHS Status (2011/65/EU) Compliant
- REACH Status Compliant
- MSL Rating (JDEC-STD-033): Not Applicable

**Packaging Details**

- Pack Style: Reel Tape & reel in accordance with EIA-481-D  
Pack Size: 1,000
- Pack Style: Bulk Loose in bulk pack  
Pack Size: 100




**Outline (mm)**



**Pad Connections**

- Crystal
  - GND & Lid
  - Crystal
  - GND & Lid
- Note: pads 2 & 4 should be connected to GND for correct operation.

**Solder Pad Layout**



**Sales Office Contact Details:**

UK: +44 (0)1460 270200  
Germany: 0800 1808 443

France: 0800 901 383  
USA: +1.760.318.2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)  
Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

Electrical Specification - maximum limiting values

Frequency Min	Frequency Max	Temperature Range	Stability (Min*)	Over Tone Order	ESR
		°C	ppm		Ω
12.0MHz	12.999999MHz	-10 to 60 -20 to 70 -40 to 85	±10 ±15 ±15	Fundamental	100
13.0MHz	18.999999MHz	-10 to 60 -20 to 70 -40 to 85	±10 ±15 ±15	Fundamental	80
19.0MHz	39.999999MHz	-10 to 60 -20 to 70 -40 to 85	±10 ±15 ±15	Fundamental	60
40.0MHz	50.0MHz	-10 to 60 -20 to 70 -40 to 85	±10 ±15 ±15	Fundamental	50

\*Stability Maximum values ±50ppm

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

**Sales Office Contact Details:**

UK: +44 (0)1460 270200  
Germany: 0800 1808 443

France: 0800 901 383  
USA: +1.760.318.2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)  
Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)