


### ISSUE 2; April 2016

#### Description




- A high frequency, low profile, miniature surface-mount oscillator consisting of a CMOS compatible hybrid circuit and a state-of-the-art fundamental-mode crystal.
- SM1 Gold Plated (RoHS)
- SM5 Solder Dipped (RoHS)
- Features:
  - Hermetically sealed ceramic package
  - Low power consumption
  - Low EMI emission
  - Optional Output Enable/Disable with Tri-State
  - Full military testing available
- Applications:
  - Military & Aerospace -
    - Smart munitions
    - Communications
    - Navigation
    - GPS
  - Industrial, Computer & Communications -
    - Miniature clock oscillator
    - Handheld instrumentation
    - PDA
    - Transponder/Animal migration
  - Medical -
    - Test & Diagnostic equipment
    - Handheld devices
- Please note that all data is only valid at 25°C unless otherwise stated.



#### Outline (mm) SM1 = Gold Plated (RoHS)



Pad Connections	Height (H) =
1. NC/EN	SM1 1.09 max
2. GND	SM3 1.21 max
3. Output	SM5 1.21 max
4. +Vs	



#### Frequency Parameters

- |                       |                         |
|-----------------------|-------------------------|
| ■ Frequency           | 1.0MHz to 160.0MHz      |
| ■ Frequency Tolerance | ±100.00ppm              |
| ■ Tolerance Condition | @ 25°C                  |
| ■ Frequency Stability | ±50.00ppm to ±100.00ppm |
| ■ Ageing              | ±5ppm max in 1st year   |

#### Electrical Parameters

- |   |             |
|---|-------------|
| ■ Supply Voltage                            | 5.0V ±10%   |
| ■ Supply Current (typical):                 |             |
| 8mA @ 24 MHz                                |             |
| 10mA @ 32 MHz                               |             |
| 13mA @ 50 MHz                               |             |
| 39mA @ 130MHz                               |             |
| ■ Supply Voltage (absolute maximum rating): | -0.5V to 7V |

#### Operating Temperature Ranges

- -10 to 70°C
- -40 to 85°C
- -55 to 125°C

#### Output Details

- |                          |      |
|--------------------------|------|
| ■ Output Compatability   | CMOS |
| ■ Drive Capability       | 15pF |
| ■ Start Up Time: 5ms max |      |

#### Sales Office Contact Details:

UK: +44 (0)1460 270200  
 Germany: 0800 1808 443

France: 0800 901 383  
 USA: +1.760.318.2824

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)  
 Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)

### Output Control

- Enable/Disable (EN):  
Logic 1 to pin 1, output enabled  
Logic 0 to pin 1, output disabled, output goes to high impedance state, current consumption low, internal oscillator stops.
- No Connection (NC):  
Pad 1 not connected internally

### Environmental Parameters

- Shock: 5000G, 0.3ms, 1/2 sine
- Vibration: MIL-STD-202G, Method 204D, Condition D: 20G rms, 10Hz-2000Hz swept sine
- Storage Temperature Range: -55 to 125°C

### Manufacturing Details

- Solder Process Temperature: 260°C max for 20sec max

### Ordering Information

- Frequency\*  
Model\*  
Termination Variant\*  
Output  
Frequency Tolerance (@ 25°C)\*  
Frequency Stability\*  
Operating Temperature Range\*  
Pad 1 Function\*  
(\*minimum required)
- Termination Variants:  
SM1 = Gold Plated / SM5 = Solder Dipped  
(Note: Non-RoHS compliant terminations also available - SM3 = Solder Dipped)
- Example  
40.0MHz CXOX 5.0V SM1  
CMOS ±100ppm ±100ppm -40 to 85C NC

### Compliance

- RoHS Status (2011/65/EU)      Compliant
- REACh Status                      Compliant
- MSL Rating (JDEC-STD-033):    Not Applicable

### Packaging Details

- Pack Style: Reel      Tape & reel in accordance with EIA-481-D  
Pack Size: 1,000
- Pack Style: Tray      Supplied on a tray  
Pack Size: 1

### Electrical Specification - maximum limiting values 5.0V ±10%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
1.0MHz	160.0MHz	-10 to 70	±50.0	39	6	40/60%
		-40 to 85	±100.0	39	6	40/60%
		-55 to 125	±100.0	39	6	40/60%

*This document was correct at the time of printing; please contact your local sales office for the latest version.*

[Click to view latest version on our website.](#)

### Sales Office Contact Details:

UK: +44 (0)1460 270200

France: 0800 901 383

Email: [info@iqdfrequencyproducts.com](mailto:info@iqdfrequencyproducts.com)

Germany: 0800 1808 443

USA: +1.760.318.2824

Web: [www.iqdfrequencyproducts.com](http://www.iqdfrequencyproducts.com)