

ISSUE 2; April 2017

Description

- Surface mount oscillator in a ceramic package, with a hermetically sealed metal lid. Suitable for Industrial applications, qualified to AEC-Q200.



Frequency Parameters

- Frequency: 4.0MHz to 110.0MHz
- Frequency Stability: $\pm 50.00\text{ppm}$ to $\pm 100.00\text{ppm}$
- Ageing: $\pm 5\text{ppm}$ max per year @ 25°C

Electrical Parameters

- Supply Voltage: 5.0V $\pm 10\%$

Operating Temperature Ranges

- 0 to 70°C
- 40 to 85°C

Output Details

- Output Compatibility: HCMOS
- Drive Capability: 15pF

Output Control

- Tri-State Operation:
Logic '1' (>90%Vs) to pad 1 enables oscillator output.
Logic '0' (<10%Vs) to pad 1 disables oscillator output; when disabled the oscillator output goes to the high impedance state.
No connection to pad 1 enables oscillator output.
- Standby Current: 10µA max

Environmental Parameters

- Storage Temperature Range: -55 to 125°C
- Qualified to AEC-Q200.

Manufacturing Details


- Maximum Process Temperature: 260°C (10secs max)

Ordering Information


- Frequency*
Model*
Output Compatibility
Frequency Stability (over operating temperature range)*
Operating Temperature Range*
Supply Voltage
(*minimum required)
- Example
10.0MHz IQXO-800
HCMOS $\pm 100\text{ppm}$ -40 to 85C 5.0V

Compliance


- RoHS Status (2011/65/EU): Compliant
- REACH Status: Compliant
- MSL Rating (JEDEC-STD-033): Not Applicable



Outline (mm)



Wave Form



Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com

Packaging Details

- Pack Style: Cutt Cut tape
Pack Size: 1
- Pack Style: Reel Tape & reel in accordance with EIA-481-D
Pack Size: 3,000

Electrical Specification - maximum limiting values 5.0V \pm 10%

Frequency Min	Frequency Max	Temperature Range	Stability (Min)	Current Draw	Rise and Fall Time	Duty Cycle
		°C	ppm	mA	ns	%
4.0MHz	9.999999MHz	0 to 70 -40 to 85	\pm 50.0 \pm 50.0	10 10	10 10	40/60% 40/60%
10.0MHz	19.999999MHz	0 to 70 -40 to 85	\pm 50.0 \pm 50.0	15 15	10 10	40/60% 40/60%
20.0MHz	29.999999MHz	0 to 70 -40 to 85	\pm 50.0 \pm 50.0	25 25	10 10	40/60% 40/60%
30.0MHz	49.999999MHz	0 to 70 -40 to 85	\pm 50.0 \pm 50.0	35 35	6 6	40/60% 40/60%
50.0MHz	79.999999MHz	0 to 70 -40 to 85	\pm 50.0 \pm 50.0	45 45	5 5	40/60% 40/60%
80.0MHz	99.999999MHz	0 to 70 -40 to 85	\pm 50.0 \pm 50.0	50 50	4.5 4.5	40/60% 40/60%
100.0MHz	110.0MHz	0 to 70 -40 to 85	\pm 50.0 \pm 50.0	55 55	3.5 3.5	40/60% 40/60%

This document was correct at the time of printing; please contact your local sales office for the latest version.

[Click to view latest version on our website.](#)

Sales Office Contact Details:

UK: +44 (0)1460 270200
Germany: 0800 1808 443

France: 0800 901 383
USA: +1.760.318.2824

Email: info@iqdfrequencyproducts.com
Web: www.iqdfrequencyproducts.com