

# WCSMC Series Crystal




- 4 Pad Plastic SMD Package
- Tuning Fork Crystal
- Tight Tolerance and Stability
- Tape and Reel Packaging



Frequency	32.768kHz
Frequency Tolerance	See Part Number Guide Below
Turnover Temperature (To)	25°C ±5°C
Frequency Stability	-0.034(±0.006)ppm/°C <sup>2</sup> (T-To) <sup>2</sup>
Operating Temperature Range	-40°C to +85°C
Storage Temperature	-55°C to +125°C
Shunt Capacitance	1.35pF Typ
Motional Capacitance	3.0fF Typ
Equivalent Series Resistance (ESR)	50K Ohms
Load Capacitance	12.5pF or 6pF
Drive Level	1μW max
Capacitance Ratio (CO/C1)	450 Typ
Aging	±3ppm / 1 <sup>st</sup> Yr Max
Insulation Resistance	500 Mega ohms Min at 100VDC ±15VDC
Hermeticity of Seal	1 x 10 <sup>-2</sup> mPa (m <sup>3</sup> /s) Max
Shock Resistance	±5ppm max (drop test onto a hard wooden board from 75cm)
Moisture Sensitivity Level	3

## Part Number Guide



Please consult with MMD sales department for any other parameters or options.




**MMD Monitor/Quartztek**  
 30400 Esperanza, Rancho Santa Margarita, CA, 92688  
 Phone: (949) 709-5075, Fax: (949) 709-3536, [www.mmdcomp.com](http://www.mmdcomp.com)  
 Sales@mmdcomp.com







Revision: 08/14/13 J

# Mechanical Details



INTERNAL CONNECTION



DIMENSION IN BRACKETS  
ARE IN INCHES

SUGGESTED  
LAND PATTERN



**MMD Monitor/Quartztek**  
30400 Esperanza, Rancho Santa Margarita, CA, 92688  
Phone: (949) 709-5075, Fax: (949) 709-3536, [www.mmdcomp.com](http://www.mmdcomp.com)  
Sales@mmdcomp.com



Revision:	08/14/13 J
-----------	------------