


# MPV5J Series

## 9x14 mm, 5.0 Volt, PECL/LVDS VCXO





- Integrated phase jitter of less than 1 ps from 12 kHz to 20 MHz
- Ideal for low noise PLL applications


Ordering Information		MPV5J	1	0	B	1	P	J	00.0000
Product Series									MHz
Temperature Range									
1:	0°C to +70°C								
2:	-40°C to +85°C								
6:	-20°C to +70°C								
8:	0°C to +50°C								
Stability									
0:	Nominal per APR selection								
Output Type									
B:	Complementary, Enable (Enable High)								
S:	Complementary, Enable (Enable Low)								
U:	Complementary Output								
Absolute Pull Range									
1:	±50 ppm (±35 ppm typ. Stability)								
8:	±25 ppm (±50 ppm typ. Stability)								
Symmetry/Output Logic Type									
P:	45/55% PECL								
Q:	40/60% PECL								
Package/Lead Configurations									
J:	J-Lead								
Frequency (customer specified)									



All dimensions in inches (mm).



### SUGGESTED SOLDER PAD LAYOUT



### Pin Connections

PIN	FUNCTION
1	Control Voltage
2	Output Enable or N/C
3	Ground/Case
4	Output Q
5	Output Q̄ or N/C
6	+Vcc

PARAMETER	Symbol	Min.	Typ.	Max.	Units	Condition
Frequency Range	F	30		800	MHz	(Consult factory for exact frequency availability)
Frequency Stability	$\Delta F/F$	(See Ordering Information)				See Note 1
Operating Temperature	TA	(See Ordering Information)				
Storage Temperature	Ts	-55		+125	°C	
Input Voltage	Vcc	4.75	5.0	5.25	V	
Input Current	Idd		60	70	mA	
Symmetry (Duty Cycle)		(See Ordering Information)				
Load						See Note 2
Rise/Fall Time	Tr/Tf		.35	.55	ns	@ 20/80% LVPECL
			.50	1.0	ns	@ 20/80% LVDS
Logic "1" Level	Voh	Vcc - 1.02			V	
Logic "0" Level	Vol			Vcc - 1.63	V	
Phase Jitter	$\phi J$					
@ 77.76 MHz			0.6	0.9	ps RMS	Integrated 12 kHz - 20 MHz
@ 155.52 MHz			0.3	0.55	ps RMS	Integrated 12 kHz - 20 MHz
@ 622.08 MHz			0.25	0.5	ps RMS	Integrated 12 kHz - 20 MHz
Phase Noise (Typical)						Offset from carrier
@ 77.76 MHz	100 Hz	1 kHz	10 kHz	100 kHz	1 MHz	dBc/Hz
@ 155.52 MHz	-80	-110	-133	-144	-147	dBc/Hz
@ 622.08 MHz	-80	-110	-133	-144	-147	dBc/Hz
	-70	-100	-125	-135	-137	dBc/Hz
Modulation Bandwidth	fm	10			Khz	-3 dB bandwidth
Input Impedance	Zin	50			K $\Omega$	
Control Voltage	Vcc	0		5.0	V	Pin 1 voltage
Center Frequency	Vc0		2.5		V	
Linearity			5	10	%	
Pullability	APR	(See Ordering Information)				See Note 3
Enable/Disable Logic		CMOS high, Vcc or N/C - enables output				Output Option B
		CMOS low or GND - disables output				
		PECL low, GND, or N/C - enables output				Output Option S
		PECL high - disables output				
Environmental	Mechanical Shock	Per MIL-STD-202, Method 213, Condition C				
	Vibration	Per MIL-STD-202, Method 201 & 204				
	Reflow Solder Conditions	240°C for 10 s max., or 230°C for 90 s max.				
	Hermeticity	Per MIL-STD-202, Method 112 (1 x 10 <sup>-8</sup> atm.cc/s of helium)				
Solderability	Per MIL-STD-883, Method 2003					

1. Stability given for deviation over temperature.
2. PECL load - see load circuit diagram #5.
3. APR specification inclusive of initial tolerance, deviation over temperature, shock, vibration, supply voltage, and aging.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see [www.mtronpti.com](http://www.mtronpti.com) for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.