





PM Surface Mount Crystals

5.0 x 7.0 x 1.3 mm



SUGGESTED SOLDER PAD LAYOUT



Available Stabilities vs. Temperature

T \ S	D	F	G	H	J	M	P
1	A	A	A	A	A	S	A
2	N	A	A	A	A	A	A
3	N	N	N	N	N	C	C
4	N	N	N	N	N	C	C
5	N	A	A	A	A	A	A
6	N	A	A	A	A	A	A

A = Available S = Standard
 N = Not Available C = Consult Factory for Availability

Ordering Information

Product Series	PM	1	M	M	XX	00.0000 MHz
Temperature Range	1: 0°C to +70°C		2: -40°C to +85°C		3: -55°C to +105°C	
	4: -55°C to +125°C		5: -10°C to +85°C		6: -20°C to +70°C	
Tolerance	D: ±10 ppm	F: ±15 ppm	G: ±20 ppm	H: ±25 ppm	J: ±30 ppm	M: ±50 ppm
Stability	D: ±10 ppm	F: ±15 ppm	G: ±20 ppm	H: ±25 ppm	J: ±30 ppm	M: ±50 ppm
	P: ±100 ppm					
Load Capacitance	Blank: 18 pF (std)					
	S: Series Resonant					
	XX: Customer Specified 10 pF to 32 pF					
Frequency (customer specified)	00.0000 MHz					

M1007Sxxx - Contact factory for datasheet.

PARAMETERS	VALUE
Frequency Range*	8.000 to 150.000 MHz
Tolerance @ +25°C	See Table Above
Stability	See Table Above
Aging	±5 ppm/yr Max
Shunt Capacitance	5 pF Max.
Load Capacitance	See ordering information
Standard Operating Conditions	See Table Above
Equivalent Series Resistance (ESR), Max.	
Fundamental (AT-cut)	
8.0000 to 10.999 MHz	60 Ω
11.000 to 13.999 MHz	50 Ω
14.000 to 15.999 MHz	40 Ω
16.000 to 40.500 MHz	30 Ω
Third Overtones (AT-cut)	
35.000 to 39.999 MHz	100 Ω
40.000 to 49.999 MHz	80 Ω
50.000 to 90.000 MHz	100 Ω
Fifth Overtones (AT-cut)	
90.000 to 150.000 MHz	100 Ω
Drive Level	100 μW Max., 50 μW Typ., 10 μW Min.
Mechanical Shock	MIL-STD-202, Method 213, C
Vibration	MIL-STD-202, Method 201 & 204
Thermal Cycle	MIL-STD, Method 1010, B
Max Soldering Conditions	See solder profile, Figure 1

* Because this product is based on AT-strip technology, not all frequencies in the range stated are available. Contact the factory for availability of specific frequencies.

MtronPTI reserves the right to make changes to the product(s) and service(s) described herein without notice. No liability is assumed as a result of their use or application.

Please see www.mtronpti.com for our complete offering and detailed datasheets. Contact us for your application specific requirements: MtronPTI 1-800-762-8800.

MtronPTI Lead Free Solder Profile

