

OW-M Type


5.0 x 3.2mm SMD CMOS Crystal Oscillator

FEATURE

- Industry Standard 5.0 x 3.2 hermetically sealed ceramic package
- Very low phase jitter: < 1 pS (0.6 pS, typ.) RMS
- Any frequency between 10 MHz and 250 MHz
- Tri-state enable/disable
- Fast delivery


TYPICAL APPLICATION

- High-Speed Gigabit Ethernet, Fiber Channel, Storage Area Network, SONET
- Enterprise Server, SAS/SATA
- Microprocessors/DSP/FPGA
- Broadband Access
- Smart Grid




RoHS Compliant

DIMENSION(mm)



SOLDER PAD LAYOUT (mm)



ELECTRICAL SPECIFICATION

Parameter	CMOS				Unit
	3.3V		2.5V		
	Min.	Max.	Min.	Max.	
Supply Voltage Variation (VDD)	VDD-5%	VDD+5%	VDD-5%	VDD+5%	V
Frequency Range	10	250	10	250	MHz
Standard Frequency	106.25, 125, 133.33, 150, 155.52 158.25, 187.5, 212.5				
Supply Current 10MHz ≤ Fo ≤ 250 MHz	-	30	-	30	mA
Output Level Output High (Logic "1") Output Low (Logic "0")	2.97	-	2.25	-	V
	-	0.33	-	0.25	
Transition Time : Rise/ Fall Time*	-	1.5	-	1.5	nSec
Start Time	-	10	-	10	mSec
Tri-State(Input to Pin 2 or Pin 1) Enable (High voltage or floating) Disable (Low voltage or GND)	2.31	-	1.75	-	V
	-	0.99	-	0.75	
RMS Phase Jitter (Integrated 12 kHz ~ 20 MHz) (At Integer Mode)	-	1.0	-	1.0	pSec
Phase Noise @125 MHz	100 Hz	-	-75	-	dBc/Hz
	1 kHz	-	-105	-	
	10 kHz	-	-120	-	
Aging (@25°C 1st year)	-	±3	-	±3	ppm
Storage Temp. Range	-55	125	-55	125	°C

*Transition times are measured between 20% and 80% of VDD

FREQ. STABILITY vs. TEMP. RANGE

Temp. (°C)	ppm	
	±25	±50
-10 ~ +60	○	○
-20 ~ +70	○	○
-40 ~ +85	△	○

* ○ : Available △ : Conditional X : Not available

* Inclusive of calibration @ 25 °C, operating temperature range, input voltage variation, load variation, aging (1st year), shock, and vibration

Note: not all combination of options are available. Other specifications may be available upon request.

Model Numbering Guide – Crystal Oscillator

Available options

Type	package (mm)	Supply Voltage(V)	Tri-State Function	Freq. Stability (ppm)	Temp. Range(°C)	Output Logic and Symmetry	Oscillator Mode	Appearance	Lead Free	Dash	Freq. (MHz)
O: Oscillator	Z:2.0 x 1.6 Y:2.5 x 2.0 X:3.2 x 2.5 V:5.0 x 3.2 C:7.0 x 5.0	E: 2.8/3.0/3.3 J: 2.5 K: 1.8 P: 1.5 L: 1.2 M: 0.9	T: Fixed-Freq with Tri-State M: Multiplier Freq with Tri-State(only for V/C package) U: Ultra Low Noise design	A: ±5 B: ±10 P: ±15 C: ±20 D: ±25 E: ±30 F: ±40 G: ±50 H: ±100	E: 0~+85 I: -10~+60 C: -20~+70 D: -30~+85 L: -40~+85 J: -40~+105 H: -40~+125 F: -55~+125	J: CMOS 15pF / 50±5% K: CMOS 15pF / 50±10%					
P: Programmable Oscillator	Y: 2.5 x 2.0 X: 3.2 x 2.5	E: 2.8/3.0/3.3 J: 2.5 K: 1.8	T: Fixed-Freq with Tri-State	C: ±20 D: ±25 G: ±50 H: ±100		J: CMOS 15pF / 50±5%	A: AT Fundamental T: AT 3rd Overtone	N: Normal	F: RoHS Compliant	-	XX.XXXXXX
O: Oscillator (Differential Output)	A: 3.2 x 2.5 W: 5.0 x 3.2 T: 7.0 x 5.0	E: 3.3 J: 2.5	T: Input to pin 2 (std.) R: Input to pin 1 (case by case) U: Ultra Low Jitter design (Only for T package)	D: ±25 G: ±50 H: ±100	I: -10~+60 C: -20~+70 D: -30~+85 L: -40~+85	L: LVPECL / 50±5% V: LVDS / 50±5% H: HCSL / 50±5%	Not Selectable by Customer				
O: Oscillator (Fast Delivery series)	W: 5.0 x 3.2 T: 7.0 x 5.0	E: 3.3 J: 2.5	M: Multiplier Freq with pin 2 Tri-State N: Multiplier Freq. with PIN 1 Tri-State	D: ±25 G: ±50 H: ±100		J: CMOS 15pF / 50±5% L: LVPECL / 50±5% V: LVDS / 50±5%					

O Y E T C C J A N F - 13.000000

*Not all combinations of options are available.

Example: OYETCCJANF-13.000000

Type	Oscillator
Package	2.5 x 2.0 mm
Supply Voltage(V)	3.3 V
Tri-State .	Fixed-Freq.
Freq. Stability	±20ppm
Temp Range	-20~+70 °C
Output	CMOS 15 pF / Symmetry 50±5%
Oscillator Mode	AT Fundamental
Appearance	Normal Appearance
Lead Free	RoHs Compliant
Frequency	13.000000 MHz