


7 x 5 mm SMD LVPECL VCXO BK SERIES



Features


- > Voltage Controlled Crystal Oscillator(VCXO).
- > PLL solution.
- > PECL output, output frequencies 100 MHz to 700 MHz.
- > Wide pull range and good linearity.
- > Low phase noise and jitter.
- > Tri-State function available.
- > Applications : SDH / SONET.
- > RoHS Compliant / Pb Free.

Electrical Specifications

Item / Type	BK
Output Type	LVPECL
Output Load	50 to VDD - 2 V
Oscillation Mode	PLL
Supply Voltage	3.3 V
Frequency Range	100 ~ 700 MHz
Frequency Stability / Operating Temperature	± 50 ppm / - 40 ~ + 85 °C
Storage Temperature Range	- 55 ~ + 125 °C
Voltage Vol (Max.) / Voh (Min.)	VDD - 1.62 V / VDD - 1.025 V
Rise (Tr) / Fall (Tf) Time (20 % ~ 80 %)	1 ns Max.
Supply Current	99 mA
Symmetry	45 ~ 55 %
Start-up Time	10 ms Max.
Absolute Pulling Range (APR) *	± 100 ppm Min. or specify
Nominal Control Voltage	1.65 V
Control Voltage Range	0 ~ 3.3 V
Linearity	± 10 % Max.
Phase Jitter (12 KHz ~ 20 MHz)	1 ps Max.


* APR=(Pull Range) - (Degrations due to initial tolerance, operating temperature, supply voltage variation and aging)

Dimensions



- PAD FUNCTION:
- 1: CONTROL VOLTAGE
 - 2: ENABLE CONTROL
 - 3: GND
 - 4: OUT
 - 5: ~OUT
 - 6: VDD

Suggested Layout
 * :External high frequency power supply decoupling required.



Units:mm

Remark : Specification subject to change without prior notice. Please confirm with our sales.